

## Technical Specifications

APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/ rail kit | SRT2200RMXLI |  
Downloaded on 01/16/2023 (EST)

# APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

SRT2200RMXLI

Call for More Information 0800 115308



- High density, double-conversion on-line power protection with scalable runtime.
- Includes: CD with software, Country-specific detachable power cord, Documentation CD, Installation guide, Rack mounting brackets, Rack mounting hardware, Rack mounting support rails, USB cable, Warranty card

Output	
Output power capacity	1.98kWatts / 2.2kVA
Max Configurable Power (Watts)	1.98kWatts / 2.2kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220 V, 240 V
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(2) IEC 60320 C19 (2) IEC 320 C19 (2) IEC Jumpers (8) IEC 60320 C13 (8) IEC 320 C13
Bypass	Built-in bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	BS1363A British, IEC 60320 C20, Schuko CEE 7 / EU1-16P
Cord Length	2.4meters
Input voltage range for main operations	100 - 275 Adjustable (half load)V
Number of Power Cords	1

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/ rail kit | SRT2200RMXL1 |  
Downloaded on 01/16/2023 (EST)



Input	
Other Input Voltages	220 V, 240 V

Batteries & Runtime	
Battery type	Lead-acid battery
Included Battery Modules	1
Typical recharge time	3hour(s)
Nominal Battery Voltage	72 V
Replacement Battery	<a href="#">APCRBC141</a>
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	122 Watts
Extendable Run Time	1
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	340Joules

Physical	
Maximum Height	85MM, 8.5CM
Maximum Width	432MM, 43.2CM
Maximum Depth	584MM, 58.4CM
Rack Height	2U
Net Weight	25.0KG
Shipping weight	34.02KG
Shipping Height	246MM, 24.6CM

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/ rail kit | SRT2200RMXL |  
Downloaded on 01/16/2023 (EST)

Physical	
Shipping Width	810MM, 81.0CM
Shipping Depth	599MM, 59.9CM
Color	Black

  

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	535.0BTU/hr
Protection Class	IP20

  

Conformance	
Approvals	CE, CE Mark, EAC, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

  

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.