

Vision Rack
VSR 800



| INPUT | |
|---------------------|-------------------------------------|
| Rated power | 800 VA |
| Voltage | 220 / 230 / 240 V |
| Frequency | 50 / 60 Hz with automatic selection |
| Frequency tolerance | ±5% Hz (3% to 10% configurable) |

| OUTPUT and INVERTER OUTPUT | |
|----------------------------|--------------------------------------|
| Rated power | 800 VA |
| Active power | 640 W |
| Waveform | Sinusoidal |
| Frequency | 50 or 60 Hz with automatic selection |

| BATTERIES | |
|-----------------------|--------------------------------------|
| Type | VRLA AGM maintenance-free lead based |
| Typical recharge time | 4-6 h |

| ENVIRONMENTAL | |
|-----------------------|---|
| Color | Black |
| Protections | Overload - short circuit - overvoltage - undervoltage - temperature - excessive low battery |
| Noise (at 1 m) | <50 [dBA] |
| Operating temperature | 0 °C - +40 °C |
| Relative humidity | 5-95% non-condensing |
| Output sockets | 4 IEC 10A |
| Standards | European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant |

| DATA | |
|--------------------|---------------|
| Weight | 12 kg |
| Dimensions (h w d) | 1Ux19"x420 mm |